

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### Product identifier

**Trade name:** Aktivator für Filtermembrane (CAT411,430)

**Synonym:** *Activator for membrane filter (CAT411,430)*

**Article number:** 71000460

### Relevant identified uses of the substance or mixture and uses advised against

*No further relevant information available.*

**Application of the substance / the mixture** *Laboratory chemicals*

### Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Endress+Hauser

Conducta GmbH+Co. KG

Dieselstraße 24

D-70839 Gerlingen

### Further information obtainable from:

Phone: +49 (0)7156 209-10117

E-Mail: [MSDS.PCC@endress.com](mailto:MSDS.PCC@endress.com)

**Emergency telephone number:** 00971 800 424 ( from 7 am to 3 pm, from Sunday to Thursday)

## SECTION 2: Hazards identification

### Classification of the substance or mixture



flame

*Flam. Liq. 2 H225 Highly flammable liquid and vapour.*



*Eye Irrit. 2 H319 Causes serious eye irritation.*

*STOT SE 3 H336 May cause drowsiness or dizziness.*

### Label elements

#### GHS label elements

*The product is classified and labelled according to the Globally Harmonised System (GHS).*

#### Hazard pictograms



GHS02 GHS07

**Signal word** *Danger*

#### Hazard-determining components of labelling:

*propan-2-ol*

#### Hazard statements

*Highly flammable liquid and vapour.*

*Causes serious eye irritation.*

*May cause drowsiness or dizziness.*

#### Precautionary statements

*Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*

*IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*

*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

(Contd. on page 2)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 1)

*Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Other hazards***The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.***Results of PBT and vPvB assessment****PBT:** *Not applicable.***vPvB:** *Not applicable.***SECTION 3: Composition/information on ingredients****Mixtures****Description:** *Mixture of substances listed below with nonhazardous additions.***Dangerous components:**

CAS: 67-63-0	propan-2-ol	30-50%
EINECS: 200-661-7	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	

**Additional information:** *For the wording of the listed hazard phrases refer to section 16.***SECTION 4: First aid measures****Description of first aid measures****General information:** *Immediately remove any clothing soiled by the product.***After inhalation:** *Supply fresh air; consult doctor in case of complaints.***After skin contact:** *Immediately rinse with water.***After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *If symptoms persist consult doctor.***Most important symptoms and effects, both acute and delayed***No further relevant information available.***Indication of any immediate medical attention and special treatment needed***No further relevant information available.***\* SECTION 5: Firefighting measures****Extinguishing media****Suitable extinguishing agents:***CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.***For safety reasons unsuitable extinguishing agents:** *no further information***Special hazards arising from the substance or mixture** *No further relevant information available.***Advice for firefighters** *No further relevant information available.***Protective equipment:** *No special measures required.***SECTION 6: Accidental release measures****Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Wear protective clothing.***Environmental precautions:***Prevent seepage into sewage system, workpits and cellars.**Dilute with plenty of water.**Do not allow to enter sewers/ surface or ground water.***Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to item 13.*

(Contd. on page 3)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 2)

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**Precautions for safe handling**

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store in a cool location.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

**\* SECTION 8: Exposure controls/personal protection**

**Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**CAS: 67-63-0 propan-2-ol**

PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
WEL (Great Britain)	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

**Ingredients with biological limit values:**

**CAS: 67-63-0 propan-2-ol**

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

**Additional information:** The lists valid during the making were used as basis.

**Exposure controls**

**Appropriate engineering controls** No further data; see item 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 3)

**Respiratory protection:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

**Hand protection***Protective gloves*

*To avoid skin problems reduce the wearing of gloves to the required minimum.*

*Only use chemical-protective gloves with CE-labelling of category III.*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

**Material of gloves**

*Nitrile rubber, NBR*

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

**Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

**Eye/face protection***Tightly sealed goggles*

**Body protection:** *Protective work clothing*

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****General Information****Physical state***Fluid***Colour:***According to product specification***Odour:***Characteristic***Odour threshold:***Not determined.***Melting point/freezing point:***Undetermined.***Boiling point or initial boiling point and boiling range***82 °C***Flammability***Not applicable.***Lower and upper explosion limit****Lower:***2 Vol %***Upper:***12 Vol %***Flash point:***< 23 °C***Ignition temperature:***425 °C***Decomposition temperature:***Not determined.***pH***Not determined.***Viscosity:****Kinematic viscosity***Not determined.***Dynamic:***Not determined.***Solubility****water:***Fully miscible.***Partition coefficient n-octanol/water (log value)***Not determined.***Vapour pressure at 20 °C:***43 hPa***Density and/or relative density****Density at 20 °C:***0.892 g/cm<sup>3</sup>*

(Contd. on page 5)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 4)

Relative density	Not determined.
Vapour density	Not determined.
<b>Other information</b>	
<b>Appearance:</b>	
Form:	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Solvent content:</b>	
Organic solvents:	50.0 %
Water:	50.0 %
Solids content:	0.0 %
<b>Change in condition</b>	
Evaporation rate	Not determined.
<b>Information with regard to physical hazard classes</b>	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

**SECTION 10: Stability and reactivity****Reactivity** No further relevant information available.**Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.**Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information**

Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity****LD/LC50 values relevant for classification:****CAS: 67-63-0 propan-2-ol**

Oral	LD50	5,045 mg/kg (rat)
------	------	-------------------

(Contd. on page 6)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 5)

Dermal	LD50	12,800 mg/kg (rbt)
Inhalative	LC50/4 h	30 mg/l (rat)

**Serious eye damage/irritation** Causes serious eye irritation.**STOT-single exposure** May cause drowsiness or dizziness.**Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**Other adverse effects****Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**SECTION 13: Disposal considerations****Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Water, if necessary together with cleansing agents.**\* SECTION 14: Transport information****UN number or ID number****IMDG, IATA**

UN1219

**UN proper shipping name****ADR**

UN1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution

**IMDG****IATA**ISOPROPANOL (ISOPROPYL ALCOHOL) solution  
Isopropanol (isopropyl alcohol) solution**Transport hazard class(es)****ADR****Class**

3 (F1) Flammable liquids.

(Contd. on page 7)

— UAE —

## Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 6)

Label 3

## IMDG, IATA



**Class** 3 Flammable liquids.  
**Label** 3  
**Packing group**  
**ADR, IMDG, IATA** II  
**Environmental hazards:** Not applicable.  
**Special precautions for user** Warning: Flammable liquids.  
**Hazard identification number (Kemler code):** 33  
**EMS Number:** F-E, S-D  
**Stowage Category** B  
**Maritime transport in bulk according to IMO instruments** Not applicable.

## Transport/Additional information:

**ADR**  
**Limited quantities (LQ)** 1L  
**Transport category** 2  
**Tunnel restriction code** D/E

## IMDG

**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml  
**UN "Model Regulation":** UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) SOLUTION, 3, II

## SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

## GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

## Hazard pictograms



GHS02 GHS07

Signal word *Danger*

## Hazard-determining components of labelling:

*propan-2-ol*

## Hazard statements

*Highly flammable liquid and vapour.**Causes serious eye irritation.**May cause drowsiness or dizziness.*

## Precautionary statements

*Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Store locked up.*

(Contd. on page 8)

**Trade name: Aktivator für Filtermembrane (CAT411,430)**

(Contd. of page 7)

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**National regulations:**

**Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** PCC-TWR

**Contact:** MSDS.pcc@endress.com

**Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*

*ICAO: International Civil Aviation Organisation*

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)*

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

\* **Data compared to the previous version altered.**