

Details for implementation of PROFIBUS-PA interface with

TMD 834

Scope

This file contains additional information to the operating manual of TMD 834.

In case the integration of a device is performed according to the profiles, compatibility and interoperability is achieved through the standardization within the profiles. In this case please refer to the PROFIBUS-PA profile specifications.

Cyclic Service of TMD 834

The telegram of the cyclic service of TMD 834 has the following format:

byte	data item	access	data format	unit
0, 1, 2, 3	Process value	Read	32-bit floating point number (IEEE-754)	°C, °F
4	Status process value	Read	z.B. 80 (hex) = device OK	---

The status is encoded in accordance with the „PROFIBUS-PA Profile for Process Control Devices“.

The status „O.K.“ is encoded as 80h (bit 7 =1; bit 0 ... bit 6 = 0).

Miscellaneous

- The implementation of the physical layer IEC 1158-2 ensures, that a reverse polarity on the signal lines has no effect on the functionality of the device.
- Suitable cables are e.g. Belden 3097A or Siemens 6XY 1830-5AH10.
- Coding of status according to „PROFIBUS-PA Profile for Process Control Devices - General Requirements“ V 2.0:

STATUS-CODE (HEX)	MEANING	DEVICE-CONDITION
0C	Device failure (means alarm, e.g. E110)	BAD
40	Non-specific (target mode switched to manual)	UNCERTAIN
80	Device OK	GOOD

- 32-bit floating point number in IEEE-754 format:

byte n			byte n+1			byte n+2			byte n+3			
bit7	bit 6	bit 0	bit7	bit 6	bit 0	bit 7		bit 0	bit 7		bit 0	
S	2^7	2^6 2^5 2^4 2^3 2^2 2^1	2^0	2^{-1} 2^{-2} 2^{-3} 2^{-4} 2^{-5} 2^{-6}	2^{-7}	2^{-8} 2^{-9} 2^{-10} 2^{-11} 2^{-12} 2^{-13} 2^{-14}	2^{-15}		2^{-16} 2^{-17} 2^{-18} 2^{-19} 2^{-20} 2^{-21} 2^{-22} 2^{-23}			
Sign	exponent			mantissa			mantissa			mantissa		

Formula: **Value** = $(-1)^S * 2^{(\text{exponent} - 127)} * (1 + \text{mantissa})$

Example: 40 F0 00 00 h = 0100 0000 1111 0000 0000 0000 0000 0000 b

$$\begin{aligned}
 \text{Value} &= (-1)^0 * 2^{(129 - 127)} * (1 + 2^{-1} + 2^{-2} + 2^{-3}) \\
 &= 1 * 2^2 * (1 + 0,5 + 0,25 + 0,125) \\
 &= 1 * 4 * 1,875 \\
 &= 7,5
 \end{aligned}$$